



PRODUCT DATA SHEET

SODIUM THIOSULFATE SOLUTION (30%)

CAS NO. 7772-98-7

CHEMICAL COMPOSITION

Sodium Thiosulfate, wt. %
Sulfite, wt. %
pH

SPECIFICATION

30 ± 2
1.5 max
7.0 – 9.0

PHYSICAL PROPERTIES

Specific Gravity @ 25 ° C
Density, lbs. /gal @ 25 ° C

1.252 – 1.340
10.4 – 11.2

DELIVERY MODE: Tank truck, tank car or 55 gallon plastic drum.

PRODUCT SAFETY INFORMATION:

Keep away from heat as the potential for release of sulfur dioxide fumes exists. Liquid sodium thiosulfate has very low toxicity but routine safety precautions should be practiced. Rubber gloves, safety goggles and protective clothing is recommended.

APPLICATIONS INCLUDE:

- Dechlorination in municipal, pulp & paper, power, and textile water treatment plants
- Oxygen scavenger – oil well drilling process
- Mining industries
- Aluminum cation reaction

INEOS CALABRIAN CORPORATION
5500 STATE HIGHWAY 366 PORT NECHES, TX 77651
Phone: (409) 727-1471
PLEASE DIRECT ALL SALES INQUIRIES BY:
PHONE: (281) 348-2303 or E-mail: ContactUs@CalabrianCorp.com

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose or as to the merchantability or fitness for a particular purpose and the manufacturer hereby expressly waives any and all such warranties. Further, the manufacturer shall not be liable for damages to person or property arising from or relating to the use, handling, or storage of Product unless damage is due to the manufacturer's negligence or willful misconduct. The manufacturer shall not be liable for damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.